Dolphin Blue Electronic Taps

Counter Mounted









DB 250/275 page 241








DB 800 / DB 825 Dolphin Blue Infrared Tap

- Touch Free Tap for ultimate hygiene prevents cross contamination
- · Quality solid brass construction with the option of two durable finished: polished chrome plating or lacquered brushed nickel plating
- Water Supply: Single inlet cold or pre-mixed a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- Flow rate 5 litres/minute (1.89 litres/minute also available - please specify)
- Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning) – for other power source options see page 270-271

- Auto adjusting sensor range 50-160 mm
- Sensor range and tap settings including optional hygiene flush and security time can be adjusted manually or by using remote control (DB51 - see page 268)
- Mandatory Hygiene Flush feature can be specified to combat Legionella
- 2 year manufacturer's warranty
- Maximum water temperature 70°C
- Operating pressure 0.5-8.0 bar (7-116 PSI)
- Interchangeable TJ M18 Neoperl Cache Aerator

Order code	Power Source	Finish	Power Co	onnections Power Source	Counter/Panel Counter/Panel	Size of hole in (Ø mm)
DB 800C	Battery (6xAA)	Polished Chrome Plating	Female	Male	min 2 max 40	min 23 max 40
DB 800S	Battery (6xAA)	Brushed Nickel Plating	Female	Male	min 2 max 40	min 23 max 40
DB 825C	9V Transformer	Polished Chrome Plating	Female	Male	min 2 max 40	min 23 max 40
DB 825S	9V Transformer	Brushed Nickel Plating	Female	Male	min 2 max 40	min 23 max 40



SPECIFICATION PHRASE

DB 800C Dolphin Blue Infrared Tap powered by battery

DB 800S Dolphin Blue Infrared Tap powered by battery

DB 825C Dolphin Blue Infrared Tap powered by 9V transformer

DB 825S Dolphin Blue Infrared Tap powered by 9V transformer