



DB 1400 / DB 1425 Dolphin Blue Panel Mounted Infra-red Tap

- Touch Free Tap – for ultimate hygiene – prevents cross contamination
- Quality solid brass construction with the option of two durable finishes: polished chrome plating or lacquered brushed nickel plating
- Water Supply: Single inlet – cold or pre-mixed – a TMV2 or TMV3 thermostatic mixing valve is recommended for premixed applications
- Flow Rate options (please specify): 5 litre/minute or 1.89 litres/minute.
- Interchangeable TT M16/18 Neoperl Aerator insert
- Power Source: Plug-in 9 Volt transformers or 9 Volt Battery (with low battery warning) –
- Auto adjusting sensor range 50-170 mm
- Sensor range and tap settings including optional hygiene flush and security time can be adjusted by using remote control (DB51)
- Mandatory Hygiene Flush feature can be specified to combat Legionella
- 2 year manufacturer's warranty
- Maximum water temperature 70°C
- Operating pressure 0.5–8.0 bar (7–116 PSI)
- **WRAS Approved product**

Product Data

- Diameter Ø 28 mm
- Projection 220mm
- Power Connections: tap female, power source male
- Counter hole Ø 23-30mm Min-max thickness 10-50mm

Product Codes

Polished chrome finish

- Powered by 6 x AAA / 9v PP3 battery **DB 1400C**
- Powered by 9v plug in transformer **DB 1425C**

Brushed nickel finish

(designed to match brushed stainless steel)

- Powered by 6 x AAA / 9v PP3 battery **DB 1400S**
- Powered by 9v plug in transformer **DB 1425S**

Related items



DB100



DB 400



WP 101



WP 111



BC 2002



WP 169