

Heatstore AFT Thermostatic Shower Specification Sheet



Technical Details

Model	AFT8X	AFT9X	AFT10X
EAN /Bar Code No.	5020669519458	5020669519465	5020669519472
Output (kW)	8.5	9.5	10.8
Current Rating (Amps)	36	40	45
Energy Rating (Class)	A	A	A
Energy Rating (%)	37	37	37
Consumption (kWh/A)	495	488	489
Load Profile	XS	XS	XS
Sound (dB)	15	15	15
Running Pressure psi (bar)	10(0.7) -140(10)	10(0.7) -140(10)	10(0.7) -140(10)
Temp Control Accuracy	±0.5 °C	±0.5 °C	±0.5 °C
Start up Temperatures	40, 41 or 43°C	40, 41 or 43°C	40, 41 or 43°C
Temperature Range	25 - 46 °C	25 - 46 °C	25 - 46 °C
IP Rating	IPX5	IPX5	IPX5
Approvals / Mark	BEAB & CE	BEAB & CE	BEAB & CE
UK Warranty (years)	5*	5*	5*

*Subject to product registration within 30 days.

Product Range

Model No:	Description	kW
AFT8X	Auto Thermostatic Shower	8.5
AFT9X	Auto Thermostatic Shower	9.5
AFT10X	Auto Thermostatic Shower	10.8


Product Description

Heatstore AFT Selectronic Premier thermostatic showers offer the highest level of temperature accuracy. This control technology combined with the many enhanced user features make them the perfect choice for Care Sector specification as well for peace of mind showering safety in any family home.

Key Features

- Highly accurate, temperature control to 0.5 °C for a safe and comfortable showering experience
- Push button controls with audible adjustment confirmation for ease of operation
- Large LED digital temperature display
- Phased shutdown safety protection for next user cool start up and scale protection
- 3 maximum temperature limiter lock options (40 °C), 41 °C), 43 °C) or unlocked (25 - 46 °C) set at installation
- Simple push button rapid commissioning
- Data logger for user and performance analysis
- Right hand side multi entry connection options
- 5 spray mode shower head with easy rub clean nozzles
- 540mm stainless steel riser rail with 4 point fixing rail brackets
- 1.25 metre anti kink flexible shower hose, adjustable handset clamp, soap dish and shower hose retaining ring

Dimensions




HEATSTORE

Tel: **+44 (0)117 923 5375**

Email: enquiries@heatstore.co.uk

Power and Water Connectivity



Pack Contents

- 1 x Instant Electric Thermostatic Shower Unit
- Shower accessory kit comprising of:
 - 1 x 540mm long 22mm diameter riser rail with 4-point fixing riser rail brackets
 - 1 x 5 mode easy rub-clean showerhead
 - 1 x 1.25m anti-kink flexible shower hose
 - 1 x Adjustable shower head holder clamp
 - 1 x Soap dish
 - 1 x Shower hose retaining ring
- 1 x Screw and wall plug fixing pack
- 1 x ErP energy rating label
- 1 x Installation and user guide

Product Packaging Data

Model	AFT8X/9X/10X
Box dimensions (mm)	580 x 325 x 145
Shower gross weight (Kg)	4.5
Shower unit net weight (Kg)	3.8
Full pallet quantity	60
Showers per layer	6

Certification

BEAB Approved	YES
BEAB CARE Approved	YES
WRAS Approved	YES
CE Marked	YES



Intertek



* Subject to product registration within 30 days.